

Silencer RLDQ/RLBQ (with baffle)

RLDQ Silencer		
Ø mm	D mm	L m
100	300	0,5 / 1 / 2
125	325	
140	340	
150	350	
160	360	
180	380	
200	400	
224	424	
250	450	
300	500	
315	515	
350	550	
400	600	
450	650	
500	700	
560	760	
630	830	
710	910	

RLBQ Silencer with Baffle		
Ø mm	D mm	L m
300	500	0,5 / 1 / 2
315	515	
350	550	
400	600	
450	650	
500	700	
560	760	
630	830	
710	910	

Temperature Rating of Product Components		
° C	Silencer	Sealants
200°	Galvanised Steel	Joka Seal Metal Sealant 2315
121°		
-20°		

Additional Notes
At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 200° C.

Compliance / Rating of Product Components		
Product	Material	Compliance / Rating
Silencer	Galvanised	DX51D with Z275 Coating
Joka Seal Metal Sealant 2315	Acetone blend	AAMA Specification 801.1

