

High Vacuum Cone / Reducer

| Ø mm | Length mm | Weight kg | Galvanised Steel |
|---------|--------------|--------------|---------------------|
| 63-50 | 67 | 0,2 | 1,5 |
| 76-50 | 70 | 0,2 | |
| 76-63 | 75 | 0,2 | |
| 102-76 | 120 | 0,4 | |
| 108-102 | 120 | 0,5 | |
| 127-76 | 120 | 0,6 | 2,0 |
| 127-102 | 120 | 0,7 | |
| 152-127 | 120 | 0,8 | |
| 203-152 | 150 | 1,4 | |

| Temperature Rating of Product Components | | |
|--|------|------------------|
| ° C | ° F | Cone / Reducer |
| 200° | 392° | Galvanised Steel |
| -20° | -4 | |

| Additional Notes |
|--|
| At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 200° C. |

| Compliance / Rating of Product Components | | |
|---|------------------|---|
| Product | Material | Compliance / Rating |
| Cone / Reducer | Galvanised steel | EN 10305 - 03 / DIN 2394 DIN 21151 NFA 49.645 BS 6323 ASTM A513/A787-5 |

